



Features

- Polystyrene core is an option in stock doors
- Most manufacturers' hinge locations
- Visible seamed edge
- Widths 2-6, 2-8, 3-0, 3-6, 4-0
- Heights 6-8, 7-0 and 8-0
- 1 ¾" only
- Prep for 3 each 4 ½" x .134 mortise hinges
- Interior or exterior usage
- 18 gauge galvanized baked-on prime finish
- 18 gauge top and bottom inverted channels

Feature Options

- Up to 3 hour fire label
- Vision lite cutout with or without channels
- Flush top cap
- Most manufacturers' Deadlock prep, Panic prep, and Mortise sectional trim
- Flat bar astragal (pairs)

Hardware Reinforcements

- 3/16" for hinges
- 12-gauge for locks standard
- 14-gauge for closers standard
- .180 heavyweight hinges allowed by field modification



Features

- Honeycomb core is standard in stock doors
- Most manufacturers' hinge locations
- Visible seamed edge
- Widths 2-6, 2-8, 3-0, 3-6, 4-0
- Heights 6-8, 7-0 and 8-0
- 1 ¾" only
- Prep for 3 each 4 ½" x .134 mortise hinges
- Interior or exterior usage
- 18 gauge galvanized baked-on prime finish
- 18 gauge top and bottom inverted channels

Feature Options

- Up to 3 hour re label
- Vision lite cutout with or without channels
- Flush top cap
- Most manufacturers' Deadlock prep, Panic prep, and Mortise sectional trim
- Flat bar astragal (pairs)

Hardware Reinforcements

- 3/16" for hinges
- 12-gauge for locks standard
- 14-gauge for closers standard
- .180 heavyweight hinges allowed by field modification